

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

# Silirub Cleanroom

---

Reference nr: 230007

Unique identification code of the product-type

**Silirub Cleanroom**

Intended use or uses of the construction product

**Sealants for facade for interior and exterior applications, intended for use in cold climate**

**Sealants used for sanitary applications**

Name and contact address of the manufacturer as required pursuant to Article 11(5)

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

Authorised Representative

**Not relevant**

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

**System 3: for reaction to fire**

**System 3: for essential characteristics**

Construction product in accordance with applicable harmonised specifications

**EN 15651-1:2012: Type F-EXT-INT-CC: 25LM**

**EN 15651-3:2012: Type XS1**

The notified body

**The notified body IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.**

# Declared Performance: EN 15651-1:2012

| Essential Characteristics                                        | Performance | Harmonised Technical Specification |
|------------------------------------------------------------------|-------------|------------------------------------|
| Reaction to fire                                                 | E           | EN 15651-1:2012                    |
| Release dangerous chemicals                                      | NPD         |                                    |
| Water and air tightness                                          |             |                                    |
| Resistance to flow                                               | ≤ 3 mm      |                                    |
| Loss of volume                                                   | ≤ 10%       |                                    |
| Tensile properties at maintained extension after water immersion | NF          |                                    |
| Secant modulus at -30°C                                          | ≤ 0.9 MPa   |                                    |
| Tensile properties at maintained extension at -30°C              | NF          |                                    |
| Durability                                                       | Pass        |                                    |

**Conditioning:** Method B

**Test Substrate:** aluminium, mortar

# Declared Performance: EN 15651-3:2012

| Essential Characteristics                                        | Performance | Harmonised Technical Specification |
|------------------------------------------------------------------|-------------|------------------------------------|
| Reaction to fire                                                 | E           | EN 15651-3:2012                    |
| Release dangerous chemicals                                      | NPD         |                                    |
| Water and air tightness                                          |             |                                    |
| Resistance to flow                                               | ≤ 3 mm      |                                    |
| Loss of volume                                                   | ≤ 10%       |                                    |
| Tensile properties at maintained extension after water immersion | NF          |                                    |
| Microbiological growth                                           | 0           |                                    |
| Durability                                                       | Pass        |                                    |

**Conditioning:** Method B

**Test Substrate:** aluminium, glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx  
Senior Technical Product Manager  
Soudal NV- Belgium

## CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

### Silirub Cleanroom



NB 0757

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr: 230007

EN 15651-1:2012

EN 15651-3:2012

Sealants for facade for interior and exterior applications, intended for use in cold climate

Sealants used for sanitary applications

#### Silirub Cleanroom

EN 15651-1:2012: Type F-EXT-INT-CC: 25LM

EN 15651-3:2012: Type XS1

**Conditioning:** Method B

**Test Substrate:** aluminium, mortar, glass

| Essential Characteristics                                        | Performance | Harmonised Technical Specification |
|------------------------------------------------------------------|-------------|------------------------------------|
| Reaction to fire                                                 | E           | EN 15651-1:2012<br>EN 15651-3:2012 |
| Release dangerous chemicals                                      | NPD         |                                    |
| Water and air tightness                                          |             |                                    |
| Resistance to flow                                               | ≤ 3 mm      |                                    |
| Loss of volume                                                   | ≤ 10%       |                                    |
| Tensile properties at maintained extension after water immersion | NF          |                                    |
| Microbiological growth                                           | 0           |                                    |
| Secant modulus at -30°C                                          | ≤ 0.9 MPa   |                                    |
| Tensile properties at maintained extension at -30°C              | NF          |                                    |
| Durability                                                       | Pass        |                                    |

## UKCA Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

### Silirub Cleanroom

---

Revision: 17-07-2025

Page 4-6

UK Reference nr DOP: 230007UK

Unique identification code of the product-type

**Silirub Cleanroom**

Intended use or uses of the construction product

**Sealants for facade for interior and exterior applications, intended for use in cold climate  
Sealants used for sanitary applications**

Name and contact address of the manufacturer as required pursuant to Article 11(5)

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

Authorised representative

**Soudal (UK) Ltd, Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth  
B77 5PN Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth B77 5PN.**

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

**System 3: for reaction to fire  
System 3: for essential characteristics**

Construction product in accordance with applicable designated standards

**BS EN 15651-1:2012: Type F-EXT-INT-CC 25LM  
BS EN 15651-3:2012: Type XS1**

Approved Body

**4ward Testing, AB 2538, has carried out Determination of the Product Type under system 3.**



**Declared Performance: BS EN 15651-1:2012**

| Essential Characteristics                                        | Performance | Designated Technical Specification |
|------------------------------------------------------------------|-------------|------------------------------------|
| Reaction to fire                                                 | E           | BS EN 15651-1:2012                 |
| Release dangerous chemicals                                      | NPD         |                                    |
| Water and air tightness                                          |             |                                    |
| Resistance to flow                                               | ≤ 3 mm      |                                    |
| Loss of volume                                                   | NPD         |                                    |
| Tensile properties at maintained extension after water immersion | NPD         |                                    |
| Secant modulus at -30°C                                          | NPD         |                                    |
| Tensile properties at maintained extension at -30°C              | NPD         |                                    |
| Durability                                                       | Pass        |                                    |

**Conditioning:** Method B

**Test substrate:** aluminium, mortar

**Declared Performance: BS EN 15651-3:2012**

| Essential Characteristics                                        | Performance | Designated Technical Specification |
|------------------------------------------------------------------|-------------|------------------------------------|
| Resistance to flow                                               | ≤ 3 mm      | BS EN 15651-3:2012                 |
| Loss of volume                                                   | NPD         |                                    |
| Water and air tightness                                          |             |                                    |
| Tensile properties at maintained extension after water immersion | NPD         |                                    |
| Microbiological growth                                           | NPD         |                                    |
| Durability                                                       | Pass        |                                    |

**Conditioning:** Method B

**Test substrate:** aluminium, glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx  
Senior Technical Product Manager  
Soudal NV- Belgium

## UKCA marking

In accordance with the CPR Regulation (EU) N° 305/2011

### Silirub Cleanroom

**UK  
CA**

AB 2538

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

21

UK Reference nr DOP: 230007UK

BS EN 15651-1:2012

BS EN 15651-3:2012

Sealants for facade for interior and exterior applications, intended for use in cold climate

Sealants used for sanitary applications

#### Silirub Cleanroom

BS EN 15651-1:2012: Type F-EXT-INT-CC 25LM

BS EN 15651-3:2012: Type XS1

**Conditioning:** Method B

**Test substrate:** aluminium, mortar

| Essential Characteristics                                        | Performance | Designated Technical Specification       |
|------------------------------------------------------------------|-------------|------------------------------------------|
| Reaction to fire                                                 | E           | BS EN 15651-1:2012<br>BS EN 15651-3:2012 |
| Release dangerous chemicals                                      | NPD         |                                          |
| Water and air tightness                                          |             |                                          |
| Resistance to flow                                               | ≤ 3 mm      |                                          |
| Loss of volume                                                   | NPD         |                                          |
| Tensile properties at maintained extension after water immersion | NPD         |                                          |
| Microbiological growth                                           | NPD         |                                          |
| Secant modulus at -30°C                                          | NPD         |                                          |
| Tensile properties at maintained extension at -30°C              | NPD         |                                          |
| Durability                                                       | Pass        |                                          |